



## LIROS Magic Race 02016

Very low stretch rope with good grip in clutches. Solid construction and excellent abrasion resistance.

- *Stretch characteristics < 1.5%*
- *very UV resistant*
- *extreme low stretch*

Ø mm	Breaking strength kg	Length of spool m
2	270	250
2.5	390	250
3	550	250
4	800	250
5	1100	250

### Colour



228  
White

**Cover** Special polyester high twisted  
2-3 mm 16-plaited  
from 4 mm 1:1-plaited

**Core** Covered Dyneema® SK78



**LIROS HSS**  
Heat Stretch System  
**LIROS LCS**  
LIROS Coating System



Sailmaker



## LIROS AntiTorsion 01442

The LIROS anti torque rope for replacing certain high load luff ropes.

- *Stretch characteristics < 1%*
- *Extremely stiff, non kinking construction with monofilament inner cover*
- *Extremely low stretch and high break load caused by Aramide core*
- *Anti torque and extremely stiff, not spliceable.*

Ø mm	Breaking strength kg	Length of spool m
6	1300	100
8	3000	100
10.5	4000	100
13	5000	100
16.5	8000	100

### Colour



205  
Silver

### Cover

Polyester 16-plaited

### Core

Aramide with monofilament cover



## LIROS V-Plus 04007

A new 100% Vectran single core rope for high load applications where minimum stretch and zero creep are essential. An innovative UV coating protects this rope from UV degradation and enhances the abrasion resistance.

- *Stretch characteristics < 1%*
- *easy to splice*
- *compact construction ensures shape retention under extreme loads*

**Material** 100% Vectran® 12-plaited with LIROS Impregnation

Ø mm	Breaking strength kg	Length of spool m
2	350	100
3	1100	100
4	1400	100
5	2800	100
6	4200	100
8	7200	100

### Colour



188  
Black

**LIROS LCS**  
LIROS Coating System



### LIROS Leach Line 01046

Compact braided, shape retaining leach line for sailmakers.

- round (therefore easy to process)
- compact
- low-shrinking

#### Colour



228 White


#### Cover

Polyester low-shrinking 16-plaited

#### Core

Polyester low-shrinking

Ø mm	Length of spool m
2	250
2.5	250
3	250
3.5	250
4	250
4.5	250
5	250
5.5	250
6	200
7	200
8	200




### LIROS Lazy Jack 01531

A new development with a hollow construction designed for quick and easy splicing. Developed for use as a Lazy Jack Rope available in 2 diameters: 4–5 mm and 6–7 mm.

- Compact and lightweight
- easy to splice
- extremely UV resistant
- easy handling

Ø mm	Breaking strength kg	Length of spool m
4–5	500	200
6–7	1100	200

#### Colour



205 Silver

#### Material

Polyester spin-dyed

#### Construction

12-plaited



### LIROS Dyneema® Webbing 00186

High tech webbing with very high strength. Multi purpose – for use on boats as well as sails and other high tenacity applications.

- lowest stretch
- high drag force
- very abrasion resistant
- no water absorption

Ø mm	Breaking strength kg	Length of spool m
25	1800	50

#### Colour



228 White

**Material** Dyneema® woven



**NEW**

## LIROS Magic Sail 01512

Ideal for sailmakers. Round construction is compact and delivers minimum shrinkage.

- *minimum shrinkage*
- *good dimensional stability*


Ø mm	Breaking strength kg	Length of spool m
2	95	100
3	185	100
4	320	100
5	680	100
6	940	100

**Material**  
Polyester

**Core**  
Polyester

**Construction**  
2-5 mm 16-plaited  
6 mm 1:1-plaited

**Colour**



236 White-Red



## LIROS Bolt Rope 00124

High quality bolt rope. High twist 3-strand Polyester with low shrink properties in white with black fleck.

- *round*
- *compact*
- *low-shrinking*

Ø mm	Length of spool m
5	250
6	200
7	200
8	200
9	200
10	200
11	200
12	200

**Colour**



228  
White

**Material** Polyester low-shrinking

**Construction** 3-strand

## LIROS Optisail 02056

The perfect new lacing line for Optis. Very low stretch, lightweight, with the ultimate in knot holding. Abrasion-resistant cover construction, with specially developed core of Dyneema® SK78.

- *Stretch characteristics < 1.5%*
- *Optimized knot tenacity*
- *LIROS-Heat-Stretch-System*
- *Available on 100m reels or in Point-of-Sale carton with 20m reels*

**Cover** Polyester

**Core** Dyneema® SK78

**Construction** 16-plaited

	Ø mm	Breaking strength kg	Length of spool m
<b>02056-0120</b>	1.2	120	100
<b>02056-2020</b>	1.2	120	20x20/Ktn.

**Colour**



199 Black-Red



LIROS HSS  
Heat Stretch System

**NEW**